



6	Screw	Steel	M2/Zn Plated
5	Spring	Stainless steel	
4	Clamp	Copper alloy	Sn Plated
3	Button	POM	UL94HB
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/8	50/8	/
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电流 / Rated Voltage(V)/Current(A)	200/9.5	250/9.5	320/9.5
额定脉冲电压 (KV) / Rate Impulse Voltage(KV)	2.5	2.5	2.5
线径范围 (硬线和软线) / Wire Range(rigid and flexible) (AWG / mm ²)	26~16/0.2~1.5		
间距 / Pitch (mm) / 线数范围 / Poles	3.50 / N=04~48P		
剥线长度 / Stripping length (mm)	10		
使用温度范围 / Operating temperature (°C)	-40~+105		
符合 RoHS 环保要求 / Conform to RoHS	Yes		

MATERIAL:

SURFACE:

MAT NO.:

STATUS:

APPD:

CHKD:

DRAFT:



宁波三安电子科技有限公司
Sanan Electrical Technology Co. Ltd

NAME: 15ESAKNHM-3.5-XXP-1Y-00A(H)

DRAWING NO.:

TYPE:

SIZE: A4

SCALE: SHEET 1/1

公差 (General tolerances) (mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
表面粗糙度 (Surface roughness)	0.1/10													
公差等级 (Tolerance grade)	±7													