



ITEM	NAME OF PART	MATERIAL	NOTES
7	Screw2	Steel	M2.5/Zn Plated
6	Screw1	Steel	M2.5/Zn Plated
5	Cage	Steel	M2.5/Zn Plated
4	Block	Steel	Zn Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL Standard	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/15	150/15	300/10
IEC 标准/IEC Standard			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	320/20	/
额定脉冲电压/电流/Rated Impulse Voltage(KV)	/	/	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)		M2.5: 0.5/4/43	
线径范围/硬线和软线/Wire Range(Rigid and flexible)(AWG/mm²)		28~12/0.2~2.5	
间距/Pitch(mm)/线数范围/Poles		5.08/N=02~24P	
剥线长度/Stripping length(mm)		9~10	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	

公差/General	tolerances(mm)
0	>3
2	>6
3	>10
6	>18
10	>30
18	>50
30	>80
50	>120
80	>180
120	>250
180	>315
250	>400
315	>500
500	>500

MATERIAL:	SURFACE:		
MAT NO.:	DRAWING NO.:		
STATUS:	SCALE:		
APPD:	SHEET		
CHKD:	REV		
DRT:	1/1		
SIZE: A4	mm	inch	
NAME: ZESAKCM-5.08-XXP-1Y-00A&Z(H)			
Sanan Electrical Technology Co., Ltd			