



3	Screw cap	Copper alloy	M2.5
2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

ITEM NAME OF PART MATERIAL NOTES	
UL 标准 / UL Standard:	B
额定电压/电流 / Rated Voltage(V)/Current(A)	300/8
EC 标准 / EC Standard:	
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	II / 2
额定电压/电流 / Rated Voltage(V)/Current(A)	250/7
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	2.5
间距 / Pitch (mm) / 线数范围 / Poles	3.50 / N=02~22P
使用温度范围 / Operating temperature(°C)	-40~+105
符合RoHS环保要求 / Conform to RoHS	Yes

MATERIAL: SURFACE:



NAME: 15ESAVM-3.5-XXP-1Y-00A(H)

MAT NO.:	APPD:	DRAWING NO.:	REV
STATUS:	CHKD:	SCALE:	SHEET
DRT:		TYPE:	1/1

公差 (General tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

0.1/10	±Z
--------	----

D

D

B

B

A

A

2

2

3

4

5

6

PCB LAYOUT